## (12) UK Patent Application (19) GB (11) 2 328 467 (13) A

(43) Date of Printing by UK Office 24.02.1999

- (21) Application No 9820642.8
- (22) Date of Filing 21.03.1997
- (30) Priority Data (31) 08621411
- (32) 25.03.1996
- (33) US
- (86) International Application Data PCT/US97/04543 En 21.03.1997
- (87) International Publication Data WQ97/36084 En 02.10.1997
- (71) Applicant(s)

Dresser Industries Inc (Incorporated in USA - Delaware) 2001 Ross Avenue, Dallas, Texas 75201, Delaware, United States of America

(72) Inventor(s)

Lee Morgan Smith

William A Goldman

- (51) INT CL<sup>6</sup>
  E21B 7/00 44/00 // E21B 47/00
- (52) UK CL (Edition Q )
  E1F FGH
  G1N NAAJA N3S7 N7H2 N7L2
- (56) Documents Cited by ISA
  US 5415030 A US 5305836 A US 4926686 A
  US 4685329 A
- (58) Field of Search by ISA
  U.S: 175/39,40; 73/152.43, 152.44, 152.45, 152.47,
  152.48
- (74) Agent and/or Address for Service
  Kilburn & Strode
  20 Red Lion Street, LONDON, WC1R 4PJ,
  United Kingdom

## (54) Abstract Title Method of assaying downhole occurrences and conditions

(57) A method of assaying work of a bit (10) of a given size and design comprises the steps of drilling a hole with the bit (10) from an initial point (I) to a terminal point (T) and recording the distance between the initial and terminal points. Electrical incremental actual force signals (18) are generated, each corresponding to a force of the bit (10) over a respective increment of the distance between the initial and terminal points. Electrical incremental distance signals (14) are also generated, each corresponding to the length of the increment for a respective one of the incremental actual force signals (18). The incremental actual force signals and incremental distance signals are processed to produce a value corresponding to the total work done by the bit in drilling from the initial point to the terminal point. Using such a work assay, a number of other downhole occurrences and/or conditions can be assayed.

